

# Print this Calibration Test page first!

Size: Height: 167.75, Bust: 92.75, Waist: 76.25, Hips: 100.25

## Notes

## How to print Printing


Once your Calibration Test Page has been printed, measure the 4"x 4" (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

## Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

## Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



Seam Allowance: 1 (3/8 in)

Pattern pieces:


1. "FRONT", MAIN FABRIC: Cut 2
2. "BACK", MAIN FABRIC: Cut 1
3. "SLEEVE", MAIN FABRIC: Cut 2
4. "FRONT BOTTOM RUFFLE", MAIN FABRIC: Cut 1
5. "BACK BOTTOM RUFFLE", MAIN FABRIC: Cut 1
6. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
8. "COLLAR STAND", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2

Pattern Specs (Circumferences are divided by 2):

1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Stretch factor horizontal 1.00 none (3/8 in)
6. Stretch factor vertical 1.00 none (3/8 in)
7. Front neck drop 8.56 cm (3 3/8 in)
8. Button diameter 1.00 cm (3/8 in)
9. Front buttons quantity 7.00 pc
10. Front length from HPS to hem 52.57 cm (20 3/4 in)
11. Across chest 49.12 cm (19 3/8 in)
12. Center front length to hem 44.20 cm (17 3/8 in)
13. Center back length to hem 49.19 cm (19 3/8 in)
14. Across front 35.47 cm (14 in)
15. Across back 35.11 cm (13 7/8 in)
16. Across shoulders 40.00 cm (15 3/4 in)
17. Side seam 24.32 cm (9 5/8 in)
18. Waist 41.71 cm (16 3/8 in)
19. Hemline sweep 48.77 cm (19 1/4 in)
20. Armhole length front 22.98 cm (9 in)
21. Armhole length back 26.98 cm (10 5/8 in)
22. Neck opening 15.21 cm (6 in)
23. Neckline length 42.97 cm (16 7/8 in)

- 24. Back neck drop 3.63 cm (1 3/8 in)
- 25. Shoulder width 12.22 cm (4 3/4 in)
- 26. Bust dart to bust dart 23.13 cm (9 1/8 in)
- 27. Sleeve length 62.92 cm (24 3/4 in)
- 28. Sleeve gather cap 13.36 cm (5 1/4 in)
- 29. Sleeve upper arm width 38.35 cm (15 1/8 in)
- 30. Sleeve opening 24.50 cm (9 5/8 in)
- 31. Ruffle front width 87.08 cm (34 1/4 in)
- 32. Ruffle back width 86.85 cm (34 1/4 in)
- 33. Ruffle length 15.00 cm (5 7/8 in)
- 34. Gather ruffle 77.30 cm (30 3/8 in)
- 35. Stand height 3.00 cm (1 1/8 in)
- 36. Collar length 42.96 cm (16 7/8 in)


Paper Size: A4;  
Print Actual Size (100% Scale);




1/1

**BACK**

**MAIN FABRIC: Cut 1**







1/2

2


1/2








1/5




2/2





2/4



2/5


**3**


**EAS**

**SLEEVE**

**MAIN FABRIC: Cut 2**

**3/1**





7


BACK NECK FACING  
MAIN FABRIC: Cut 1  
FUSIBLE INTERFACING: Cut 1

6

FRONT NECK FACING

MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2




3/4


3/5

4/1




4/2





4/4



4/5



5/1

HEM 3/8"  
(1) cm


4

**FRONT BOTTOM RUFFLE**


**MAIN FABRIC: Cut 1**



5/2



5/3



**GATHER**

5/4

8

COLLAR STAND  
MAIN FABRIC: Cut 2  
FUSIBLE INTERFACING: Cut 2

FOLD



5/5



5

**BACK BOTTOM RUFFLE**

**MAIN FABRIC: Cut 1**

6/1

6/2

6/3

GATHER

6/4



6/5

