

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 82.5, Waist: 66, Hips: 90.25

Notes

How to print Printing

Once your Calibration Test Page has been printed, measure the 4"x 4" (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



Seam Allowance: 1 (3/8 in)

Pattern pieces:


1. "FRONT", MAIN FABRIC: Cut 2
2. "BACK", MAIN FABRIC: Cut 1
3. "SLEEVE", MAIN FABRIC: Cut 2
4. "FRONT BOTTOM RUFFLE", MAIN FABRIC: Cut 1
5. "BACK BOTTOM RUFFLE", MAIN FABRIC: Cut 1
6. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
8. "COLLAR STAND", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2

Pattern Specs (Circumferences are divided by 2):

1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Stretch factor horizontal 1.00 none (3/8 in)
6. Stretch factor vertical 1.00 none (3/8 in)
7. Front neck drop 8.30 cm (3 1/4 in)
8. Button diameter 1.00 cm (3/8 in)
9. Front buttons quantity 6.00 pc
10. Front length from HPS to hem 50.99 cm (20 1/8 in)
11. Across chest 44.00 cm (17 3/8 in)
12. Center front length to hem 42.89 cm (16 7/8 in)
13. Center back length to hem 48.97 cm (19 1/4 in)
14. Across front 30.61 cm (12 in)
15. Across back 33.21 cm (13 1/8 in)
16. Across shoulders 38.44 cm (15 1/8 in)
17. Side seam 27.07 cm (10 5/8 in)
18. Waist 36.53 cm (14 3/8 in)
19. Hemline sweep 43.05 cm (17 in)
20. Armhole length front 19.77 cm (7 3/4 in)
21. Armhole length back 23.42 cm (9 1/4 in)
22. Neck opening 14.70 cm (5 3/4 in)
23. Neckline length 41.63 cm (16 3/8 in)

- 24. Back neck drop 3.60 cm (1 3/8 in)
- 25. Shoulder width 11.81 cm (4 5/8 in)
- 26. Bust dart to bust dart 20.84 cm (8 1/4 in)
- 27. Sleeve length 62.06 cm (24 3/8 in)
- 28. Sleeve gather cap 12.21 cm (4 3/4 in)
- 29. Sleeve upper arm width 34.87 cm (13 3/4 in)
- 30. Sleeve opening 21.46 cm (8 1/2 in)
- 31. Ruffle front width 74.01 cm (29 1/8 in)
- 32. Ruffle back width 79.37 cm (31 1/4 in)
- 33. Ruffle length 15.00 cm (5 7/8 in)
- 34. Gather ruffle 68.17 cm (26 7/8 in)
- 35. Stand height 3.00 cm (1 1/8 in)
- 36. Collar length 41.63 cm (16 3/8 in)


Paper Size: LETTER;
Print Actual Size (100% Scale);




1/1


BACK

MAIN FABRIC: Cut 1





1/3



3


SLEEVE

MAIN FABRIC: Cut 2



HEM 3/8"
(1 cm)


1/4




1/5




2/1



2/2




2/3



2/4

2/5



3/1

8

COLLAR STAND
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2



5

BACK BOTTOM RUFFLE

MAIN FABRIC: Cut 1



3/2

FOLD




3/3


GATHER

3/4

EASE




3/5



4/1

4


FRONT BOTTOM RUFFLE
MAIN FABRIC: Cut 1



4/2

GATHER

4/3



4/4




4/5

6

FRONT NECK FACING

MAIN FABRIC: Cut 2

FUSIBLE INTERFACING: Cut 2




5/1

1


FRONT

MAIN FABRIC: Cut 2





5/2



K NECK FACING
LIN FABRIC: Cut 1

7

5/3

5/4


5/5



6/1



6/2



6/3

6/4

6/5

