

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 114.25, Waist: 99, Hips: 120.75

Notes

How to print Printing

Once your Calibration Test Page has been printed, measure the 4"x 4" (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



Seam Allowance: 1 (3/8 in)

Pattern pieces:


1. "FRONT", MAIN FABRIC: Cut 2
2. "BACK", MAIN FABRIC: Cut 1
3. "SLEEVE", MAIN FABRIC: Cut 2
4. "FRONT BOTTOM RUFFLE", MAIN FABRIC: Cut 1
5. "BACK BOTTOM RUFFLE", MAIN FABRIC: Cut 1
6. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
8. "COLLAR STAND", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2

Pattern Specs (Circumferences are divided by 2):

1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Stretch factor horizontal 1.00 none (3/8 in)
6. Stretch factor vertical 1.00 none (3/8 in)
7. Front neck drop 9.26 cm (3 5/8 in)
8. Button diameter 1.00 cm (3/8 in)
9. Front buttons quantity 7.00 pc
10. Front length from HPS to hem 56.97 cm (22 3/8 in)
11. Across chest 60.06 cm (23 5/8 in)
12. Center front length to hem 47.88 cm (18 7/8 in)
13. Center back length to hem 50.93 cm (20 in)
14. Across front 44.81 cm (17 5/8 in)
15. Across back 38.02 cm (15 in)
16. Across shoulders 42.82 cm (16 7/8 in)
17. Side seam 23.19 cm (9 1/8 in)
18. Waist 53.32 cm (21 in)
19. Hemline sweep 60.29 cm (23 3/4 in)
20. Armhole length front 26.03 cm (10 1/4 in)
21. Armhole length back 30.40 cm (12 in)
22. Neck opening 16.55 cm (6 1/2 in)
23. Neckline length 46.61 cm (18 3/8 in)


- 24. Back neck drop 3.76 cm (1 1/2 in)
- 25. Shoulder width 12.71 cm (5 in)
- 26. Bust dart to bust dart 27.54 cm (10 7/8 in)
- 27. Sleeve length 63.52 cm (25 in)
- 28. Sleeve gather cap 16.45 cm (6 1/2 in)
- 29. Sleeve upper arm width 46.60 cm (18 3/8 in)
- 30. Sleeve opening 27.00 cm (10 5/8 in)
- 31. Ruffle front width 117.09 cm (46 1/8 in)
- 32. Ruffle back width 100.41 cm (39 1/2 in)
- 33. Ruffle length 15.00 cm (5 7/8 in)
- 34. Gather ruffle 96.66 cm (38 in)
- 35. Stand height 3.00 cm (1 1/8 in)
- 36. Collar length 46.61 cm (18 3/8 in)


Paper Size: LETTER;
Print Actual Size (100% Scale);




1/1

MAIN FABRIC: Cut 1








1/4

1

FRONT


MAIN FABRIC: Cut 2





FRONT NECK FACING

MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2









2/1




2/2

)


2/3



2/4



2/5



2/6



2/7

C

SLEEVE


MAIN FABRIC: Cut 2



3/1

3/2

EASE



3/3

8



COLLAR STAND
MAIN FABRIC: C&F 2
FUSIBLE INTERFACING: C&F 2




3/4

FOLD

3/5




3/6




3/7

4/1



4/2

4/3



4/4


4/5

4/6

4/7

5/1


FRONT B
MAIN



5/2




HEM 3/8"
(1) cm



5/3

GATHER

5/4




5/5



5/6



5/7



4

OTTOM RUFFLE

FABRIC: Cut 1

6/1

5

BACK BOTTOM RUFFLE

MAIN FABRIC: Cut 1

•

6/2



6/3

GATH

6/4



ER



6/5

6/6



6/7

7/1

7/2

7/3





7/4

7/5

7/6

7/7