

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 87.75, Waist: 71.25, Hips: 95.25

Notes

How to print Printing

Once your Calibration Test Page has been printed, measure the 4"x 4" (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



Seam Allowance: 1 (3/8 in)

Pattern pieces:


1. "FRONT", MAIN FABRIC: Cut 2
2. "BACK", MAIN FABRIC: Cut 1
3. "SLEEVE", MAIN FABRIC: Cut 2
4. "FRONT BOTTOM RUFFLE", MAIN FABRIC: Cut 1
5. "BACK BOTTOM RUFFLE", MAIN FABRIC: Cut 1
6. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
7. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
8. "COLLAR STAND", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2

Pattern Specs (Circumferences are divided by 2):

1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Stretch factor horizontal 1.00 none (3/8 in)
6. Stretch factor vertical 1.00 none (3/8 in)
7. Front neck drop 8.44 cm (3 3/8 in)
8. Button diameter 1.00 cm (3/8 in)
9. Front buttons quantity 7.00 pc
10. Front length from HPS to hem 51.70 cm (20 3/8 in)
11. Across chest 46.62 cm (18 3/8 in)
12. Center front length to hem 43.45 cm (17 1/8 in)
13. Center back length to hem 49.24 cm (19 3/8 in)
14. Across front 33.16 cm (13 in)
15. Across back 34.16 cm (13 1/2 in)
16. Across shoulders 39.42 cm (15 1/2 in)
17. Side seam 25.62 cm (10 1/8 in)
18. Waist 39.15 cm (15 3/8 in)
19. Hemline sweep 45.88 cm (18 1/8 in)
20. Armhole length front 21.51 cm (8 1/2 in)
21. Armhole length back 25.35 cm (10 in)
22. Neck opening 14.96 cm (5 7/8 in)
23. Neckline length 42.36 cm (16 5/8 in)

- 24. Back neck drop 3.61 cm (1 3/8 in)
- 25. Shoulder width 12.08 cm (4 3/4 in)
- 26. Bust dart to bust dart 22.03 cm (8 5/8 in)
- 27. Sleeve length 62.54 cm (24 5/8 in)
- 28. Sleeve gather cap 12.65 cm (5 in)
- 29. Sleeve upper arm width 36.48 cm (14 3/8 in)
- 30. Sleeve opening 23.34 cm (9 1/4 in)
- 31. Ruffle front width 80.55 cm (31 3/4 in)
- 32. Ruffle back width 82.94 cm (32 5/8 in)
- 33. Ruffle length 15.00 cm (5 7/8 in)
- 34. Gather ruffle 72.66 cm (28 5/8 in)
- 35. Stand height 3.00 cm (1 1/8 in)
- 36. Collar length 42.35 cm (16 5/8 in)


Paper Size: LETTER;
Print Actual Size (100% Scale);




1/1

BACK

MAIN FABRIC: Cut 1








1/2

2

1/3





1/4


EASE


3

SLEEVE


MAIN FABRIC: Cut 2

1/5






2/2




2/3



2/4



2/5



3/1

8

COLLAR STAND
MAIN FABRIC: Cut 2
FUSIBLE INTERFACING: Cut 2

5

BACK BOTTOM RUFFLE

MAIN FABRIC: Cut 1

3/2

FOLD

3/3


GATHER

3/4

HEM 3/8"
(1) cm



3/5



4/1


4

FRONT BOTTOM RUFFLE
MAIN FABRIC: Cut 1



↓
4/2

GAT




4/3

HER

BACK
MAIN
FUSIBLE 1


4/4



4/5



5/1




6

FRONT NECK FACING

MAIN FABRIC: Cut 2

FUSIBLE INTERFACING: Cut 2


5/2




5/3

NECK FACING
FABRIC: CUT 1
INTERFACING: CUT 1

7





5/4

5/5

T


FRONT

FABRIC: Cut 2



6/1

→ S/2



6/3

6/4

6/5