

Print this Calibration Test page first!

Size: Height: 167.75, Bust: 90.25, Waist: 73.75, Hips: 98

Notes

How to print Printing


Once your Calibration Test Page has been printed, measure the 4"x 4" (10cm) scale box with a ruler. If the lengths match, you can confidently print your pattern. If the rulers do not match, set your print settings to 100% or Actual and retry.

Cutting

Your printouts will always have a dashed border to perfectly match your sheets. Cut off the right edge of each page. Be careful not to cut beyond the dashed mark, otherwise your patterns will not align accurately.

Tapping

Group each sheet by the second number marked on each pate i.e. in a group 1, there are: 1/1, 2/1, 3/1, 4/1, etc. In a group 2: 1/2, 2/2 etc. 2. Place page 1/1 on top of the page 2/1, overlapping the right side edge. Match corners and crosses and secure with a pin or tape. Then use a scotch tape to permanently attach the sheets together.



Seam Allowance: 1 (3/8 in)

Pattern pieces:


1. "FRONT", MAIN FABRIC: Cut 2
2. "BACK", MAIN FABRIC: Cut 1
3. "SLEEVE", MAIN FABRIC: Cut 2
4. "FRONT NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2
5. "BACK NECK FACING", MAIN FABRIC, FUSIBLE INTERFACING: Cut 1
6. "COLLAR STAND", MAIN FABRIC, FUSIBLE INTERFACING: Cut 2

Pattern Specs (Circumferences are divided by 2):

1. Hem max 3.00 none (1 1/8 in)
2. Seam allowance max 2.00 none (3/4 in)
3. Seam allowance p max 1.50 none (5/8 in)
4. Stretch factor 1.00 none (3/8 in)
5. Stretch factor horizontal 1.00 none (3/8 in)
6. Stretch factor vertical 1.00 none (3/8 in)
7. Front neck drop 8.48 cm (3 3/8 in)
8. Button diameter 1.00 cm (3/8 in)
9. Front buttons quantity 8.00 pc
10. Across chest 47.88 cm (18 7/8 in)
11. Waist 38.99 cm (15 3/8 in)
12. Hips 52.74 cm (20 3/4 in)
13. Front length from HPS to hem 67.70 cm (26 5/8 in)
14. Center front length to hem 59.41 cm (23 3/8 in)
15. Center back length to hem 64.92 cm (25 1/2 in)
16. Across front 33.87 cm (13 3/8 in)
17. Across back 34.87 cm (13 3/4 in)
18. Across shoulders 39.78 cm (15 5/8 in)
19. Side seam 40.65 cm (16 in)
20. Hemline sweep 52.22 cm (20 1/2 in)
21. Armhole length front 22.25 cm (8 3/4 in)
22. Armhole length back 26.21 cm (10 3/8 in)
23. Neck opening 15.04 cm (5 7/8 in)
24. Neckline length 42.56 cm (16 3/4 in)
25. Back neck drop 3.62 cm (1 3/8 in)


- 26. Shoulder width 12.20 cm (4 3/4 in)
- 27. Bust dart to bust dart 23.04 cm (9 1/8 in)
- 28. Sleeve length 58.03 cm (22 7/8 in)
- 29. Sleeve upper arm width 31.23 cm (12 1/4 in)
- 30. Sleeve opening 23.65 cm (9 1/4 in)
- 31. Sleeve cap length 49.73 none (19 5/8 in)
- 32. Stand height 3.00 cm (1 1/8 in)
- 33. Collar length 42.56 cm (16 3/4 in)


Paper Size: LETTER;
Print Actual Size (100% Scale);



1/1

MAIN FABRIC: Cut 1







1/2

2

BACK





1/4


EASE

MAIN FABRIC: Cut 2



SLEEVE

3

1/5




2/1



2/2




2/3



2/4



2/5



3/1




5


BACK NECK FACING
MAIN FABRIC: CUT 1
RUSKLE INTERFACING: CUT 1



3/2



3/3



3/4


1

FRONT

MAIN FABRIC: Cut 2



3/5



4


FRONT NECK FACING

MAIN FABRIC: Cut 2


FUSIBLE INTERFACING: Cut 2

4/1

4/2



4/3



4/5




5/1




5/2

5/3






5/5




6/1




6/2

6/3



6/4



FOLD

6

COLLAR STAND
MAIN FABRIC: CUT 2
FUSIBLE INTERFACING: CUT 2

6/5

